HIGOLD

A Series A-shaped rotating shoe rack

Installation manual

A Series

Model

Accessories list

A series A-shaped rotating shoe rack is compatible with 4 accessories. The specific accessories are as follows:

Layers No.	No. of plate	No. of base	Overall size
3	3	1	1150*1150
4	4	1	1150*1150
5	5	1	1150*1150
6	6	1	1150*1150
7	7	1	1150*1150
8	8	1	1150*1150

Accessories List

Upper slide rail/ Lower slide rail*1

Rotating frame *1/ Column* 4/ 6 Expanding screw/ Hexagon wrench*1

Handle *1/ Locking decorative cover *1

M5*10mm hexagon socket screw *4/ M5 gasket *4/ M5 locking washer *4/ M5 nut *4/ Tool Device screws *2/ Mini screw*4/ 3.15x19.76mm self-tapping screws *4/ Installation manual *1

Installation of lower slide rail

Remove the screws on the top and bottom of the column

Align the installation hole on the rail with a screw hole of the column and use the screws to install. Align and tighten M5 nuts.

Slide the bottom hole of the lower slide rail to expose the screw hole, position it as per the installation drawing.

Use 3.15x19.76mm self-tapping screws to align with the pre-drilled holes and lock the slide rail.

Finish the installation of lower slide rail.

Installation of upper slide rail

Similarly, take the same tools of the top of the column.

Align the installation hole on the rail with the screw hole of the column and use the screws to install. Align and tighten M5 nuts.

Slide the bottom hole of the upper slide to expose the screw hole, position it as per the installation drawing.

Use 3.15x19.76mm self-tapping screws to align with the pre-drilled holes and lock the upper slide.

Finish the installation of upper slide.

Installation of frame

Align the bottom holes of the rotating frame with the groove holes of the slide and fix the rotating frame with M5 hexagon socket screws with M5 gaskets.

Use M5 M5*10mm hexagon socket screws at the bottom, and the bottom of the main frame frame to fix it.

Adjust the adjustable screw on both sides of the rotating frame to align the screw holes on the upper end of the frame with the hole position in the groove of the upper slide rail.

Use M5 M5*10mm hexagon socket screws with M5 gaskets to connect and fix the upper end of the frame and the upper slide, and then tighten the screws.

Tighten the support screws of the adjustable screws on the frame and lock the nuts.

Installation of the interlocking components

Connect the interlocking components to the connecting rod and fix them.

Insert the M5*L rotating washer into the hole of the interlocking connector, and then use the M5 locking washer that is the same as the M5 nut to fix the bottom of the main frame, and fix the bottom side with the nut.

Tighten the M5 nut and hexagon wrench to fix it firmly.

Insert the M5 rotating washer into the upper linkage, turn the position, then insert the M5 locking washer into the top connection part, and then use the wrench and the nut to lock with it.

The upper connecting rod has been installed, and the frame is as shown in fact.

Installation of the basket

Align the hook on the side of the basket with each plate of the frame and press down to insert it firmly. Rest the side with the guard plate of the basket is aligned with the frame and.

Finally, the basket has installed a total of 6 baskets, and the installation is completed. Note: The installation of the basket is not limited to the number of three baskets. The basket installation is complete.

Installation of the handle

Align the hole the holes with the frame holes, and then use the screws to install the handle. The handle installation is complete.

Finish the A series A-shaped rotating shoe rack installation.

HIGOLD